## megamount 503/503 Racing FULL-AUTOMATIC

"An unbeatably priced, run-flat capable tyre changer that is at home in any type of environment."

Offers the versatility, rigidity and speed of operation of a fully automatic machine




#### **MAIN FEATURES**

- Pneumatic forward/back swinging mounting arm.
- Pneumatic supported step-back of the mounting arm.
- Clamping range 10-24 inches
- Inflating pressure limiting device.
- Smart blade bead breaker, also for the stiffest tyres.
- Mounting column with 41mm diameter.
- Megafit 2 all functions combined in one arm.(Racing)



Two Clamping Cylinders
For a powerful clamping also for the big
tires and RunFlat tires.





Universal shovel

The special form of the bead breaker shovel requires no protection blade. It is made to fit all rims without scratching.

## Standard Features coming with the machine:

- Oiler (+Water separator Racing)
- Grease pot holder
- Tyre lever

- 10 bar operating pressure limiting device
- CE 3,5 bar inflating pressure limiting device
- Plastic protection package

# megamount 503/503 Racing full-automatic

### Standard Features and Optional Accessories

### **Optional Accessories**



#### **JetBlast**

This device helps seat the bead of stubborn sidewalls when inflating. Fully integrated in the machine. Replaces the GT device.




#### QX-System

Forget the lever! Pneumatic supported mounting/dismounting tool for fast and safe working. To convert a standard machine into 'lever-less' operation. (tilt arm models only).



#### **Exchangeable Mounting Heads**

This patented system is the original and still the best, requiring no tools just a straight forward changeover by hand. The system provides complete coverage for all types of rim and tyre, including standard/low profile/run-flat, raised spoke and plastic heads.



TECHNICAL DATA	
Air pressure	8 to 12bar
Three phase Motor	230-400V /50Hz /550W
Motor single phase (Option)	
Self-centring lock external	10"-22"
Self-centering lock internal	12"-24"
Maximal wheel diameter	1000mm
Maximal rim width	13"
Bead breaker pressure	2500kg (single sided)
Dim.s, (WxDxH) 503/503+Megafit2	76x98x107 / 113x138x186
Weight (packed) 503/503+ Megafit2	229kg / 323kg